

SPECIFICATIONS

材质Material:

绝缘体 (Insulator): Polyester (UL94V-0)
Standard: PA6T Black

接触件Contacts: Brass

接触电镀Contact Plating: Au or Sn over 30 μ" Ni

电气性能Electrical Characteristics:

接触电阻Contact Resistance: 20mΩ Max.

绝缘电阻Insulator Resistance: 1000MΩ Min.


耐电压Withstanding Voltage: AC 500V

额定电流Current Rating: 1.5 AMP




适用温度范围Operating Temperature: -40℃ to +105℃

工作温度Working Temperature: -25℃ to +85℃




耐温性能Temperature resistance: 255℃ ± 5℃, 3s-5s max



Unit:mm



PCB LAYOUT



订购方法 How To Order

2.0排针	H	B	XX	S/R	T/A	G 0	XXX
Plastics Height H=1.0mm H=1.5mm H=2.0mm		Material Type A=PBT B=Nylon-6T C=LCP D=Nylon-46	NO. of Positions Per Row 02 thru 80	S: Straight(180°) R: Right Angle(90°) M: S.M.T	T: TIN(镀锡) A: Aureate (镀金)	Contact Plating SN: Tin G0: Gold Flash G2: 5u" Gold G3: 10u" Gold G4: 15u" Gold G5: 30u" Gold S0: Gold Flash/Tin Standard: G0	Pin Length (PC外露) XXX=A+B+H XXX=A+B+H+C+1.00 (短针)

常规表达: 型号(2.0双排针座)-胶芯高度(H)-材质(PA6T)-规格(2*XXP)-类型(S/R)-接触件镀层(XXU")-尺寸(XXX)

* 其它要求的产品另外说明 Other requests's product on the other hand description