

SPECIFICATIONS

材质Material:

绝缘体 (Insulator): Polyester (UL94V-0)
Standard: PA6T Black

接触件Contacts: Brass

接触电镀Contact Plating: Au or Sn over 30μ" Ni

电气性能Electrical Characteristics:

接触电阻Contact Resistance: 20mΩ Max.


绝缘电阻Insulator Resistance: 1000MΩ Min.

耐电压Withstanding Voltage: AC 500V






额定电流Current Rating: 1.5 AMP

适用温度范围Operating Temperature: -40℃ to +105℃

耐温性能Temperature resistance: 255℃ ± 5℃, 3s-5s max



Unit:mm



PCB LAYOUT

订购方法 How To Order

2.0排针	H	B	XX	S/R	T/A	G 0	XXX
Plastics Height H=4.0mm		Material Type A=PBT B=Nylon-6T C=LCP D=Nylon-46	NO. of Positions Per Row 02 thru 80	S: Straight(180°) R: Right Angle(90°) M: S.M.T	T: TIN(镀锡) A: Aureate (镀金)	Contact Plating SN: Tin G0: Gold Flash G2: 5u" Gold G3: 10u" Gold G4: 15u" Gold G5: 30u" Gold S0: Gold Flash/Tin Standard: G0	Pin Length XXX=A+B+4.00 XXX=A+B+2.70 (短针)

常规表达: 型号 (2.0双排针座) - 胶芯高度(H) - 材质 (PA6T) - 规格 (2*XXP) - 类型 (S/R) - 接触件镀层 (XXU") - 尺寸 (XXX)

* 其它要求的产品另外说明 Other requests's product on the other hand description