

SPECIFICATIONS

材质Material:

绝缘体 (Insulator): Polyester (UL94V-0)
Standard: PBT Black

接触件Contacts: Brass

接触电镀Contact Plating: Au or Sn over 30 μ" Ni

电气性能Electrical Characteristics:

接触电阻Contact Resistance: 20mΩ Max.



绝缘电阻Insulator Resistance: 1000MΩ Min.

耐电压Withstanding Voltage: AC 500V

额定电流Current Rating: 3 AMP

适用温度范围Operating Temperature: -40℃ to +105℃

耐温性能Temperature resistance: 205℃ ± 5℃, 3s-5s max



订购方法 How To Order

2.54排针	H	A	XX	S/R	T/A	G 0	XXX
Plastics Height H=1.0mm H=1.5mm H=2.0mm H=2.5mm		Material Type A=PBT B=Nylon-6T C=LCP D=Nylon-46	NO. of Positions Per Row 02 thru 80	S: Straight (180°) R: Right Angle (90°) M: S.M.T	T: TIN (镀锡) A: Aureate (镀金)	Contact Plating SN: Tin G0: Gold Flash G2: 5u" Gold G3: 10u" Gold G4: 15u" Gold G5: 30u" Gold S0: Gold Flash/Tin Standard: G0	Pin Length (PC外露) XXX=A+B+C XXX=A+B+C+D +2H-1.00 (长针)

常规表达: 型号 (2.54双排针座) - 胶芯高度 (H) - 材质 (PBT) - 规格 (2*XXP) - 类型 (S/R) - 接触件镀层 (XXU") - 尺寸 (XXX)

* 其它要求的产品另外说明 Other requests's product on the other hand description