

VERSION	VERSION OF THIS DESCRIPTION	DATE
A	NEW DRAWINGS ISSUED	2021/12/30
B	DESIGN CHANGES	2021/12/31

技术参数 (SPECIFICATIONS)

材料 (Material):


Insulator: PBT/PA6T (UL94V-0), Black
绝缘体 (外壳): PBT/PA6T (防火等级V-0), 黑色
Contacts: Brass/Phosphor Bronze
接触件: 黄/磷青铜
Plating: Gold Flash/SN over 30 μ" Ni
电镀: 30 μ" 镍底上镀金/锡

电气特性 (Electrical Characteristics):

Contact Resistance: 20mΩ Max.
接触电阻: 20mΩ Max.
Insulator Resistance: 1000MΩ Min.
绝缘电阻: 1000MΩ Min.
Withstanding Voltage: AC 500V
耐压值: AC 500V
Current Rating: 1 AMP
额定电流: 1 AMP
Operating Temperature range: -40°C to +105°C
适用温度范围: -40°C to +105°C
Spacing: 1.27
间距: 1.27

After Assembly

未标明公差按公差分段

塑胶材质	电镀处理	UNITS	SCALE	APPROVED	DESIGN	PRODUCT NAME	FC 1.27*1.27-XXP		
PBT/PA6T	Gold Flash	MM	4:1	ZHAOZHEN JIANG	CHEN YUN	eyeconn [®]	深圳市超越世纪电子有限公司		
公差 分段	>10 <10 < 3	±0.30 ±0.25 ±0.10	 THE THIRD PERSPECTIVE		PARTS DRAWING		PAGES	1/1	Drawing A4